



EXTERIOR LUXURY EMULSION

BUILT FOR BEAUTIFUL EXTERIORS

WEATHER SEAL ULTIMATE PROTECT

A fresh, attractive finish for properly prepared and primed exterior walls.

7-YEAR WARRANTY

EXTERIOR WALLS



20 L / 10 L / 5 L / 4 L / 1 L

A lasting first impression

A simple exterior finish begins with the right preparation and a coordinated colour choice.



THE RIGHT FINISH STARTS WITH A SOUND SURFACE

Designed for new painting and repainting on clean, fully cured, repaired and primed exterior walls.

WHY CHOOSE ULTIMATE PROTECT?

01

Exterior-focused

Formulated for exterior wall application.

02

New & repainting

Suitable for fresh projects and repainting.

03

Surface preparation

Used with the recommended putty and primer system.

04

Shade-ready

Two finish coats; three recommended for dark shades.

AVAILABLE PACK SIZES

20 L 10 L 5 L 4 L 1 L

The beautiful finish process

Follow the recommended surface preparation, priming and painting sequence.

01 CLEAN

Remove dirt, fungus and loose particles using detergent, a wire brush or sandpaper. Wash thoroughly.

02 REPAIR

Fill holes, dents and cracks with Sarvottam Wall Putty. Sand the surface smooth and wipe clean.

03 CURE

Allow freshly plastered surfaces to cure fully before priming.

04 FIRST PRIMER COAT

Apply Sarvottam Paints Exterior Wall Primer. Let it dry for 6-8 hours.

05 SECOND PRIMER COAT

Dilute the primer with 35% water and apply the second coat.

06 PAINT FINISH

Apply two coats of Weather Seal Ultimate Protect. Allow 4-6 hours between paint coats.

07 DARK SHADES

Apply three paint coats for optimal results when using dark shades.

RECOATING INTERVAL

Allow 4-6 hours between paint coats.

The details that matter

Recommended specification and quick answers for planning your project.

PRODUCT SPECIFICATIONS

Product type	Exterior Emulsion
Application area	Exterior walls
Surface condition	Clean, cured, repaired & primed
Recommended putty	Sarvottam Wall Putty
Recommended primer	Sarvottam Exterior Wall Primer
Primer coats	2
First primer drying	6-8 hours
Second primer dilution	35% water
Standard paint coats	2
Dark-shade paint coats	3
Interval between paint coats	4-6 hours

FREQUENTLY ASKED QUESTIONS

Can it be used on new plaster?

Yes, after the plaster is fully cured and the surface has been prepared and primed.

How many paint coats should I apply?

Two for standard application; three for dark shades.

How long between paint coats?

Allow 4-6 hours between applications.

7 YEARS PRODUCT WARRANTY

SARVOTTAM PAINTS